ATEN Technology, Inc.
www.aten-usa.com

PS/2 Mini Desktop KVM w/cables CS82AC

The CS82AC is a simple, convenient solution for multi-computer management. It allows you to switch between two PS/2 equipped computers using one mouse, keyboard, and monitor.

There are two convenient methods for switching between computers: Buttons on the front panel of the switch or simple hotkey strokes directly from the keyboard.

The KVM has built in emulation on the mouse and keyboard ports which eliminate errors when booting, and to ensure their instantaneous recognition when switching computers.

There is no software to install, so set up is merely a matter of connecting the included cables between your computers and the CPU ports, then connecting your mouse, monitor, and keyboard to the color coded console ports.

Other features include a durable metal case, support for video resolutions up to 1920 x 1440 (DDC2B compliant), no power adapter to lose, and it is compatible with WIN 2K, WIN XP, WIN 2003, LINUX, and virtually all PS/2 compliant operating systems.

Distributor Part NO. : Contact Aten for part number @ 949.428.1111

Features:

- Use one keyboard, monitor and mouse to control up to two computers
- Works with PS/2 compliant computers
- Operating system independent
- Supports video resolutions up to 2048 x 1536
- Easy to install - no software required
- Easy to operate - push buttons or Hot Keys
- Keyboard and mouse emulation for error free computer booting
- Built in AutoScan mode to monitor all computers
- LEDs allow for easy status monitoring
- Increases desk space and productivity
- Decreases power and equipment costs
- Trim-line, compact design
- 7 Year Limited Warranty

Requirements:

- PS/2 keyboard and mouse
- VGA or multi-sync monitor
- PS/2 compliant computers

Package Content:

- 1 CS84A KVM switch
- 2 Premium Bonded KVM Cables
- 1 User Manual
- 1 Registration Card
- 1 Quick Start Guide

Specification :

Physical Properties	
Unit Package Dimensions	6.8 x 9.4 x 2.4 in [17.3 x 23.9 x 6.1 cm]
* Housing	Metal
Case Weight	24.2 lbs [11 kg]
Unit Weight	0.925 lbs [0.42 kg]
Case Dimension	7.5 x 13 x 19.5 in [19.0 x 33.0 x 50 cm]
Unit Dimension	5.5 x 3.4 x 2.2in [14.0 x 8.7 x 5.5 cm]
Unit Weight with package	2.3 lbs [1 kg]
Case Qty	10
Environment	
Storage Temperature	-4~140°F [-20°~60°C]
Humidity	0~80% RH, Non-condensing
Operation Temperature	32~122 °F [0°~50°C]
Switches	
Port Selection	2 x Pushbutton
Computer Connections	
Direct	2
Emulation	
Mouse	PS/2
Keyboard	PS/2
LEDs	
On Line	2 (Orange)
Selected	2 (Green)
Console Connectors	
Mouse	1 x 6-pin Mini-DIN Female (Green)
Monitor	1 x HDB-15 Female (Blue)

Keyboard	1 x 6-pin Mini-DIN Female (Purple)
CPU Connectors	
Keyboard	2 x 6-pin Mini-DIN Female (Purple)
Monitor	2 x HDB-15 Male (Blue)
Mouse	2 x 6-pin Mini-DIN Female (Green)
Video Resolution	1920 x 1440; DDC2B
Power Connections	1 x DC Jack (Black)
Scan Interval	3, 5, 10, 20 Seconds
Port Selection	Hotkey, Pushbutton
Power Consumption	DC9V, 1.08W